

ASME A112.18.8-2020
[Revision of ASME A112.18.8-2009 (R2014)]

Sanitary Waste Valves for Plumbing Drainage Systems

AN AMERICAN NATIONAL STANDARD



**The American Society of
Mechanical Engineers**

ASME A112.18.8-2020
[Revision of ASME A112.18.8-2009 (R2014)]

Sanitary Waste Valves for Plumbing Drainage Systems

AN AMERICAN NATIONAL STANDARD



**The American Society of
Mechanical Engineers**

Two Park Avenue • New York, NY • 10016 USA

Date of Issuance: October 21, 2020

This Standard will be revised when the Society approves the issuance of a new edition.

ASME issues written replies to inquiries concerning interpretations of technical aspects of this Standard. Interpretations are published on the Committee web page and under <http://go.asme.org/InterpsDatabase>. Periodically certain actions of the ASME A112 Committee may be published as Cases. Cases are published on the ASME website under the A112 Committee Page at <http://go.asme.org/A112committee> as they are issued.

Errata to codes and standards may be posted on the ASME website under the Committee Pages to provide corrections to incorrectly published items, or to correct typographical or grammatical errors in codes and standards. Such errata shall be used on the date posted.

The A112 Committee Page can be found at <http://go.asme.org/A112committee>. There is an option available to automatically receive an e-mail notification when errata are posted to a particular code or standard. This option can be found on the appropriate Committee Page after selecting "Errata" in the "Publication Information" section.

ASME is the registered trademark of The American Society of Mechanical Engineers.

This code or standard was developed under procedures accredited as meeting the criteria for American National Standards. The Standards Committee that approved the code or standard was balanced to assure that individuals from competent and concerned interests have had an opportunity to participate. The proposed code or standard was made available for public review and comment that provides an opportunity for additional public input from industry, academia, regulatory agencies, and the public-at-large.

ASME does not "approve," "rate," or "endorse" any item, construction, proprietary device, or activity.

ASME does not take any position with respect to the validity of any patent rights asserted in connection with any items mentioned in this document, and does not undertake to insure anyone utilizing a standard against liability for infringement of any applicable letters patent, nor assume any such liability. Users of a code or standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, is entirely their own responsibility.

Participation by federal agency representative(s) or person(s) affiliated with industry is not to be interpreted as government or industry endorsement of this code or standard.

ASME accepts responsibility for only those interpretations of this document issued in accordance with the established ASME procedures and policies, which precludes the issuance of interpretations by individuals.

No part of this document may be reproduced in any form,
in an electronic retrieval system or otherwise,
without the prior written permission of the publisher.

The American Society of Mechanical Engineers
Two Park Avenue, New York, NY 10016-5990

Copyright © 2020 by
THE AMERICAN SOCIETY OF MECHANICAL ENGINEERS
All rights reserved
Printed in U.S.A.

CONTENTS

Foreword	iv
Committee Roster	v
Correspondence With the A112 Committee	vi
1 General	1
2 General Requirements	2
3 Testing	3
4 Marking, Identification, and Instructions	7
Figures	
2.4.1-1 Typical Cross Section	2
3.1.1-1 Waterway Flow-Rate Test Apparatus	3
3.4.1-1 Inversion Recovery Test Apparatus	5
3.11.1-1 Life-Cycle Test Apparatus	7

FOREWORD

In 2004, the initial work on a standard for “self-sealing waterless waste valves” was undertaken by a Committee of the International Association of Plumbing and Mechanical Officials (IAPMO), in accordance with a request from a manufacturer. Their efforts resulted in their Interim Guide Criteria, IGC 203-2004, which was used as a benchmark for performance of such devices, which are now known as “sanitary waste valves.” IGC 203-2004 was submitted to the ASME Standards Committee A112, Plumbing Materials and Equipment, for conversion into an American National Standard. A112 Project Team 18.8 was established for the purpose of undertaking this task.

The purpose of this Standard is to establish a generally acceptable standard for sanitary waste valves for installation on tubing. Its purpose is to serve as a guide for producers, distributors, architects, engineers, contractors, installers, inspectors, and users; to promote understanding regarding materials, manufacture, and installation; and to provide for identifying fittings for installation on valves complying with this Standard.

Sanitary waste valves are intended for use as an alternative to tubular p-traps. Sanitary waste valves provide a waterless barrier between the waste system and the fixture.

ASME A112.18.8-2009 (R2014) was up for reaffirmation in 2018 [letter ballot (LB) 18-3314] along with two other ASME standards, but it was disapproved (record 18-2614). A revised draft incorporating comments resulting from the initial ballot was subsequently disapproved.

The A112.18.8 Project Team met on October 23, 2019, and based on the comments received at this teleconference meeting, created a revised draft. The further-revised draft was issued for consideration (LB 19-459), resulting in several disapproval comments requiring resolution. Additional modifications were proposed to address these outstanding disapproval comments and suggestions. The revised draft was recirculated (LB 19-2160 RC1), and the resulting standard was approved by the A112 Committee on January 30, 2020.

This Standard has been strengthened and improved based on the various comments and inputs received. This edition includes the following revisions:

- (a) The term “In-Line” has been deleted from the title.
- (b) In [para 3.2](#), the test pressure limit has been increased from 2 in. water, gage, to 4 in. water, gage, and the time/duration interval has been increased from 10 sec to 20 sec. Additionally, the protocol now incorporates twice the actual testing of the valve.
- (c) The internal references to ANSI/ASSE 1051-2009 have been corrected and now reflect the appropriate test sections for minimum airflow.

This Standard was approved by the American National Standards Institute on June 8, 2020.

ASME A112 COMMITTEE

Standardization of Plumbing Materials and Equipment

(The following is the roster of the Committee at the time of approval of this Standard.)

STANDARDS COMMITTEE OFFICERS

W. M. Smith, *Chair*
S. Rawalpindiwala, *Vice Chair*
A. L. Guzman Rodriguez, *Secretary*

STANDARDS COMMITTEE PERSONNEL

R. K. Adler, City of San Jose
J. A. Ballanco, JB Engineering and Code Consulting
J. E. Bertrand, Fortune Brands Global Plumbing Group
T. Burger, NSF International
R. Burnham, Zurn Industries, LLC
M. Campos, ICC Evaluation Service, LLC
W. E. Chapin, Professional Code Consulting, LLC
P. V. DeMarco, IAPMO Group
N. E. Dickey, Hansgrohe, Inc.
G. S. Duren, Code Compliance, Inc.
R. Emmerson, Consultant
K. Ernst, OS&B
R. L. George, Plumb-Tech Design and Consulting Services, LLC
D. Gleiberman, Sloan Valve Co.
M. Guard, Regulosity, LLC
A. L. Guzman Rodriguez, The American Society of Mechanical Engineers
C. Haldiman, Watts Water Technologies
G. W. Harrison, Consultant
L. Himmelblau, Chicago Faucet
J. M. Koeller, Koeller and Co.
C. J. Lagan, American Standard/LIXIL
W. LeVan, Cast Iron Soil Pipe Institute
D. Marbry, Fluidmaster, Inc.
R. Mata, American Society of Plumbing Engineers
L. A. Mercer, IAPMO Group
A. Murra, Abraham Murra Consulting
D. Orton, NSF International
A. Poon, Delta Faucet Co.
S. Rawalpindiwala, Kohler Co.
S. A. Remedios, Remedios Consulting
M. Sigler, Plumbing Manufacturers International
G. L. Simmons, Charlotte Pipe & Foundry
W. M. Smith, American Society of Plumbing Engineers
J. C. Watson, Elkay Manufacturing
M. Weiss, Plumbing & Drainage Institute
W. C. Whitehead, Whitehead Consulting Services
A. Ciechanowski, *Alternate*, NSF International
M. R. Gibeault, *Alternate*, Kohler Co.
J. W. Lauer, *Alternate*, Sloan Valve Co.
M. Malatesta, *Alternate*, American Standard/LIXIL
C. W. McDonald, *Alternate*, Fortune Brands Global Plumbing Group
W. B. Morris, *Alternate*, Charlotte Pipe & Foundry
K. Thompson, *Alternate*, IAPMO Group
S. L. Cavanaugh, *Contributing Member*, Cavanaugh Consulting
J. Kendzel, *Contributing Member*, American Supply Association
N. M. Kummerlen, *Contributing Member*, Consultant
D. Liang, *Contributing Member*, CSA Group
R. Pickering, *Contributing Member*, Eastern Research Group, Inc.
L. Pilla, *Contributing Member*, CSA Group
B. Ramkarran, *Contributing Member*, Infinity Drain, Ltd.
S. Tanner, *Contributing Member*, U.S. Environmental Protection Agency

A112.18.8 PROJECT TEAM PERSONNEL — SANITARY WASTE VALVES

G. S. Duren, *Chair*, Code Compliance, Inc.
M. Campos, ICC Evaluation Service, LLC
D. M. Clayson, Wavin, Ltd.
G. Dobson, Wavin B.V.
R. L. George, Plumb-Tech Design and Consulting Services, LLC
D. Gleiberman, Sloan Valve Co.
G. W. Harrison, Consultant
J. M. Koeller, Koeller and Co.
W. B. Morris, Charlotte Pipe & Foundry
D. Orton, NSF International
J. Tanner, Flow-Liner Systems, Ltd.
M. Weiss, Plumbing & Drainage Institute

CORRESPONDENCE WITH THE A112 COMMITTEE

General. ASME Standards are developed and maintained with the intent to represent the consensus of concerned interests. As such, users of this Standard may interact with the Committee by requesting interpretations, proposing revisions or a case, and attending Committee meetings. Correspondence should be addressed to:

Secretary, A112 Standards Committee
The American Society of Mechanical Engineers
Two Park Avenue
New York, NY 10016-5990
<http://go.asme.org/Inquiry>

Proposing Revisions. Revisions are made periodically to the Standard to incorporate changes that appear necessary or desirable, as demonstrated by the experience gained from the application of the Standard. Approved revisions will be published periodically.

The Committee welcomes proposals for revisions to this Standard. Such proposals should be as specific as possible, citing the paragraph number(s), the proposed wording, and a detailed description of the reasons for the proposal, including any pertinent documentation.

Proposing a Case. Cases may be issued to provide alternative rules when justified, to permit early implementation of an approved revision when the need is urgent, or to provide rules not covered by existing provisions. Cases are effective immediately upon ASME approval and shall be posted on the ASME Committee web page.

Requests for Cases shall provide a Statement of Need and Background Information. The request should identify the Standard and the paragraph, figure, or table number(s), and be written as a Question and Reply in the same format as existing Cases. Requests for Cases should also indicate the applicable edition(s) of the Standard to which the proposed Case applies.

Interpretations. Upon request, the A112 Standards Committee will render an interpretation of any requirement of the Standard. Interpretations can only be rendered in response to a written request sent to the Secretary of the A112 Standards Committee.

Requests for interpretation should preferably be submitted through the online Interpretation Submittal Form. The form is accessible at <http://go.asme.org/InterpretationRequest>. Upon submittal of the form, the Inquirer will receive an automatic e-mail confirming receipt.

If the Inquirer is unable to use the online form, he/she may mail the request to the Secretary of the A112 Standards Committee at the above address. The request for an interpretation should be clear and unambiguous. It is further recommended that the Inquirer submit his/her request in the following format:

Subject:	Cite the applicable paragraph number(s) and the topic of the inquiry in one or two words.
Edition:	Cite the applicable edition of the Standard for which the interpretation is being requested.
Question:	Phrase the question as a request for an interpretation of a specific requirement suitable for general understanding and use, not as a request for an approval of a proprietary design or situation. Please provide a condensed and precise question, composed in such a way that a "yes" or "no" reply is acceptable.
Proposed Reply(ies):	Provide a proposed reply(ies) in the form of "Yes" or "No," with explanation as needed. If entering replies to more than one question, please number the questions and replies.
Background Information:	Provide the Committee with any background information that will assist the Committee in understanding the inquiry. The Inquirer may also include any plans or drawings that are necessary to explain the question; however, they should not contain proprietary names or information.

Requests that are not in the format described above may be rewritten in the appropriate format by the Committee prior to being answered, which may inadvertently change the intent of the original request.

Moreover, ASME does not act as a consultant for specific engineering problems or for the general application or understanding of the Standard requirements. If, based on the inquiry information submitted, it is the opinion of the Committee that the Inquirer should seek assistance, the inquiry will be returned with the recommendation that such assistance be obtained.

ASME procedures provide for reconsideration of any interpretation when or if additional information that might affect an interpretation is available. Further, persons aggrieved by an interpretation may appeal to the cognizant ASME Committee or Subcommittee. ASME does not “approve,” “certify,” “rate,” or “endorse” any item, construction, proprietary device, or activity.

Attending Committee Meetings. The A112 Standards Committee regularly holds meetings and/or telephone conferences that are open to the public. Persons wishing to attend any meeting and/or telephone conference should contact the Secretary of the A112 Standards Committee. Future Committee meeting dates and locations can be found on the Committee Page at <http://go.asme.org/A112committee>.

INTENTIONALLY LEFT BLANK

SANITARY WASTE VALVES FOR PLUMBING DRAINAGE SYSTEMS

1 GENERAL

1.1 Scope

This Standard establishes minimum requirements for materials in the construction of a sanitary waste valve (hereinafter referred to as “the valve”) for use as an alternate to a tubular p-trap. This Standard prescribes minimum test requirements for the performance of the valve together with methods of marking and identification. This Standard does not define the requirements for products to be used in urinals or water closets. It is not intended that products meeting this Standard will be used in a urinal or water closet.

The provisions of this Standard are not intended to prevent the use of any alternate material or method of construction provided any such alternate meets the intent of this Standard.

1.2 Units of Measurement

Values are stated in U.S. Customary units and in the International System of Units (SI). The U.S. Customary units shall be considered as the standard.

In this Standard, gallons (U.S. liquid) per minute is abbreviated gpm, and liters (metric liquid) per minute is abbreviated L/min.

1.3 References

The following documents form a part of this Standard to the extent specified herein. Unless otherwise specified, the latest edition shall apply.

ANSI/ASSE 1051-2009, Individual and Branch Type Air Admittance Valves for Plumbing Drainage Systems
 Publisher: American Society of Sanitary Engineering (ASSE), 901 Canterbury Road, Westlake, OH 44145
 (www.asse-plumbing.org)

ASME A112.18.2/CSA B125.2, Plumbing Waste Fittings
 ASME B1.20.1, Pipe Threads, General Purpose (Inch)
 Publisher: The American Society of Mechanical Engineers (ASME), Two Park Avenue, New York, NY 10016-5990
 (www.asme.org)

ASTM D2000, Standard Classification System for Rubber Products in Automotive Applications
 ASTM D2661, Standard Specification for Acrylonitrile-Butadiene-Styrene (ABS) Schedule 40 Plastic Drain, Waste, and Vent Pipe Fittings
 ASTM D2665, Standard Specification for Poly(Vinyl Chloride) (PVC) Plastic Drain, Waste, and Vent Pipe and Fittings
 ASTM F409, Standard Specification for Thermoplastic Accessible and Replaceable Plastic Tube and Tubular Fittings
 Publisher: American Society for Testing and Materials (ASTM International), 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959 (www.astm.org)

1.4 Definitions

bladder/checking member: the component of the sanitary waste valve that provides the sealing function.

sanitary waste valve: a product used as an alternate to a water-filled tubular waste trap that provides protection for the property from foul air in the sewer.

2 GENERAL REQUIREMENTS

2.1 Material

The valve shall meet the material requirements of ASTM F409. The valve shall be installed in an accessible location.

2.2 Seal Material

Seal materials shall comply with or exceed classification M3BA507 A14 B13 C12 F17 or M2BG714 B14 E014 E034 of ASTM D2000.

2.3 Bladder/Checking Member Material

Bladder/checking member material shall comply with or exceed classification M3FC607 EA14 E016 G11 of ASTM D2000.


2.4 Valve Inlet

2.4.1 The valve inlets shall be 1¹/₄ in. (31.8 mm) or 1¹/₂ in. (38.1 mm) nominal straight or with an 87¹/₂-deg elbow or be standard pipe size straight inlets (see Figure 2.4.1-1).

2.4.2 The base of the thread may be sealed by a sealing washer (inlet set) at the base of the thread. The useful thread length shall be between 3³/₈ in. (9.5 mm) and 1¹/₂ in. (12.7 mm). All threaded fixture outlets shall have a minimum three-thread engagement for fittings and plastic nuts to correctly engage and energize the inlet seal in accordance with ASTM F409.

2.4.3 If required for horizontal installations, an 87¹/₂-deg knuckle adapter shall be available to allow the valve to be connected in a horizontal position. When installed in a horizontal position, the device and connected piping shall have a minimum slope of 1:48 [i.e., 1¹/₄ in./ft (21 mm/m)].

Figure 2.4.1-1 Typical Cross Section



GENERAL NOTE: The above images are for illustrative purposes only.

2.4.4 If required, a straight-running adapter shall be available to allow the valve to be connected to the pipe rather than the fixture outlet.

2.5 Valve Outlet

The valve outlet shall have a connection that is compatible with tubing or pipe complying with ASTM F409, ASTM D2661, or ASTM D2665 or threaded connections complying with ASME A112.18.2/CSA B125.2.

2.6 Threaded Connections


All threads that connect to external fixtures shall comply with ASME B1.20.1.

3 TESTING

3.1 Waterway Flow Rate

3.1.1 Test Method. Connect the valve to the waste outlet hole of the tank in accordance with [Figure 3.1.1-1](#) and the manufacturer’s installation instructions. Fill the test tank with water up to the test level. Stabilize the test level by adjusting the water inflow by means of the regulating valve. When the test water level is stabilized, the flow rate of the valve is indicated by the flowmeter.

Figure 3.1.1-1 Waterway Flow-Rate Test Apparatus



3.1.2 Performance Requirements. The valve shall demonstrate flow rates not less than

- (a) 1¼ in. (31.8 mm): 9.5 gpm (36 L/min), valve alone on wash basin, bidet
- (b) 1½ in. (38.1 mm): 13.5 gpm (51 L/min), valve alone on bath
- (c) 1½ in. (38.1 mm): 11.1 gpm (42 L/min), valve alone on kitchen sink

3.2 One-Way Sealing Performance of the Valve

3.2.1 Test Apparatus. The test apparatus is as follows:

- (a) length of ¼ in. (6 mm) bore rubber tubing
- (b) tee-junction suitable for use with the rubber tubing
- (c) u-tube manometer with a range of 0 in. (0 mm) to 6 in. (152 mm) of water, gage
- (d) reducer to enable the rubber tube to be connected to the outlet of the valve

3.2.2 Test Method. Prime the valve by running a gallon of water through the valve to waste. Connect the rubber tubing through the reducer to the outlet of the valve. Connect the other end of the tube to the tee-junction, one leg of which is connected to the u-tube manometer and the remaining leg to another length of tubing. Apply air pressure to the free end of the tubing until a pressure of 4 in. (102 mm) of water, gage, is registered on the u-tube manometer. Clamp the end of the tube and maintain pressure for 20 sec. Release the pressure and leave the valve and equipment in situ for a minimum of 48 hr, then retest under the same conditions but omit the water priming stage.

3.2.3 Performance Requirements. The valve shall retain a seal under a back pressure, equivalent to 4 in. (102 mm) of water, gage, for 20 sec on both the initial test (with valve primed) and the retest.

3.3 Airway Flow Rate

3.3.1 Test Method. The airway flow rate test shall be performed in accordance with ANSI/ASSE 1051-2009, paras. 3.2.2 through 3.2.3.

3.3.2 Performance Requirements. The maximum opening pressure of the device shall meet the requirements of ANSI/ASSE 1051-2009, para. 3.2.4. The measured airflow rate shall be at least 1 ft³/min (0.47 L/s) in accordance with the requirements for 1¼-in. and 1½-in. drainage systems in ANSI/ASSE 1051-2009, para. 1.2.3 and Table 1.

3.4 Recovery From an Excess Back Pressure (Inversion) Condition

3.4.1 Test Method. Fit the valve to be tested to a standard sink and connect the arrangement of pipe work shown in [Figure 3.4.1-1](#) to the outlet of the valve. Close valve at point B. Slowly open valve C until the bladder inverts and water flows into the sink. Record the pressure at the point of inversion. Close valve C; open valve B. Insert the sink plug and fill the sink with water to level A.

NOTE: Failure of the bladder to invert shall not constitute a failure of the test or a reason to stop the test.

3.4.2 Performance Requirements. When the sink plug is removed, the sink shall completely drain. At the completion of the test in [para. 3.4.1](#), the valve shall be tested in accordance with [paras. 3.1](#) and [3.2](#). Failure to achieve the performance parameters prescribed in [paras. 3.1](#) and [3.2](#) shall be cause for rejection of the valve.

3.5 Leak Tightness


3.5.1 Test Method. The valve shall be tested in accordance with the hydrostatic pressure test in ASTM F409 using an internal pressure of 25 psi (172 kPa) for 1 hr.

3.5.2 Performance Requirements. The valve shall show no evidence of leakage and demonstrate air tightness.

3.6 Thermal Cycling

3.6.1 Test Requirement. The valve shall complete the following thermal cycling test procedure for 5 cycles and allow 5 sec of draining time between cycles:

- (a) 7.9 gpm (30 L/min) of water at a temperature of 203°F ± 4°F (95°C ± 2°C) over a period of 15 min at a constant flow rate
- (b) 7.9 gpm (30 L/min) of water at a temperature of 68°F ± 10°F (20°C ± 5°C) over a period of 10 min at a constant flow rate

Figure 3.4.1-1 Inversion Recovery Test Apparatus**Legend:**

- A = water level
- B = outlet drain valve
- C = inlet valve
- D = pressure gage
- I = valve under test

3.6.2 Performance Requirements. At the completion of the above test, the valve shall be tested in accordance with [para. 3.2](#) and meet the requirements of [para. 3.2.3](#).

3.7 Cyclic Fatigue

3.7.1 Test Requirement. The valve shall complete the following cyclic fatigue test procedure allowing 60 sec for draining between cycles: 1,500 cycles of 60 sec \pm 2 sec duration, at a temperature of 200°F \pm 4°F (93°C \pm 2°C) followed by 60 sec at a temperature of 59°F \pm 10°F (15°C \pm 5°C), flow rate 7.9 gpm \pm 0.1 gpm (30 L/min \pm 0.5 L/min).

3.7.2 Performance Requirements. At the completion of the above test, the valve shall be tested in accordance with [para. 3.2](#) and meet the requirements of [para. 3.2.3](#).

3.8 Resistance to Household Substances

3.8.1 Test Apparatus. The valve shall be attached to a sink fitted with a standard crosspiece outlet.

3.8.2 Substances to Be Tested. A separate test shall be carried out for each of the following five materials. For each test, a 1.5-oz (43-g) or 1.5-fl. oz. (44-mL) sample of material shall be used.

- (a) material 1: food — uncooked long-grain rice
- (b) material 2: food — diced vegetable of size $\frac{1}{4}$ in. \times $\frac{1}{4}$ in. \times $\frac{1}{4}$ in. (6 mm \times 6 mm \times 6 mm)
- (c) material 3: cleaners — liquid soaps
- (d) material 4: solids — kiln-dried sand
- (e) material 5: lard — 95% water, 5% melted lard, each at 150°F (65.6°C)

3.8.3 Test Method. Place the material on or around the sink outlet. Pour 4 pt [64 fl oz (1.9 L)] onto the material to flush the material from the sink. Use cold water for materials 1 through 4; use warm water at 150°F (65.6°C) for material 5. Leave the system for 24 hr.

3.8.4 Performance Requirements. At the completion of the above test, the valve shall be tested in accordance with [para. 3.2](#) and meet the requirements of [para. 3.2.3](#).

3.9 Resistance to Chemicals and Solvents

3.9.1 Test Requirement. The valve shall be attached to a sink fitted with a standard crosspiece outlet.

3.9.2 Substances to Be Tested. Each test shall be carried out separately using a quantity of $\frac{3}{4}$ pt [12 fl oz (0.35 L)] of one of the following solvents:

- (a) solvent 1: liquid drain cleaner containing sulfuric acid
- (b) solvent 2: mineral spirits
- (c) solvent 3: kerosene

3.9.3 Test Method. Pour the solvent into the sink outlet. After 1 min, pour 4 pt [64 fl oz (1.9 L)] of cold water into the sink outlet to flush the solvent from the sink. Leave the system for 24 hr.

3.9.4 Performance Requirements. At the completion of the above test, the valve shall be tested in accordance with [para. 3.2](#) and meet the requirements of [para. 3.2.3](#).

3.10 Drop

3.10.1 Test Method. The test shall be conducted over a clean concrete surface. Hold the valve with the lowest point upside down 3 ft (0.91 m) above the surface and release the valve. Pick up the valve and change orientation (top uppermost) and release onto concrete again. Pick up the valve one final time and change orientation (sideways) and release onto concrete. Observe the valve for any changes.


3.10.2 Performance Requirements. The valve shall show no signs of deformation or breakage that may affect its function.

3.11 Life Cycle

3.11.1 Test Requirement. The valve's resistance to cyclic fatigue under ambient conditions shall be tested using the apparatus shown in [Figure 3.11.1-1](#).

3.11.2 Test Method. The valve shall undergo 20,000 cycles. A cycle comprises 10 sec of exposure to water followed by 10 sec of draining.

3.11.3 Performance Requirements. At the completion of the above test, the valve shall be tested in accordance with [para. 3.2](#).

Figure 3.11.1-1 Life-Cycle Test Apparatus

4 MARKING, IDENTIFICATION, AND INSTRUCTIONS

4.1 Marking and Identification

The valve shall be permanently and legibly marked with the following:

- (a) manufacturer's name
- (b) product name or brand name
- (c) nominal size of inlet and outlet
- (d) date of manufacture
- (e) predominant material
- (f) direction of flow indicator
- (g) indication of the orientation of the installation of the device

4.2 Instructions

The manufacturer shall provide instructions on packaging or accompanying literature indicating, where appropriate, both of the following:

- (a) orientation of the installation of the device
- (b) limitations on the use and type of drain-cleaning chemicals and tools

INTENTIONALLY LEFT BLANK

A112 ASME STANDARDS RELATED TO PLUMBING

A112.1.2-2012 (R2017)	Air Gaps in Plumbing Systems (For Plumbing Fixtures and Water-Connected Receptors)
A112.1.3-2000 (R2019)	Air Gap Fittings for Use With Plumbing Fixtures, Appliances, and Appurtenances
A112.3.1-2007 (R2017)	Stainless Steel Drainage Systems for Sanitary, DWV, Storm, and Vacuum Applications, Above- and Below-Ground
A112.3.4-2000 (R2004)	Macerating Toilet Systems and Related Components
A112.4.1-2009 (R2019)	Water Heater Relief Valve Drain Tubes
A112.4.2-2015/CSA B45.16-15 (R2020)	Personal Hygiene Devices for Water Closets
A112.4.3-1999 (R2019)	Plastic Fittings for Connecting Water Closets to the Sanitary Drainage System
A112.4.4-2017	Plastic Push-Fit Drain, Waste, and Vent (DWV) Fittings
A112.4.7-2002 (R2008)	Point of Use and Branch Water Submetering Systems
A112.4.14-2004 (R2010)	Manually Operated, Quarter-Turn Shutoff Valves for Use in Plumbing Systems
A112.6.1M-1997 (R2017)	Floor-Affixed Supports for Off-the-Floor Plumbing Fixtures for Public Use
A112.6.2-2017	Framing-Affixed Supports (Carriers) for Off-the-Floor Plumbing Fixtures
A112.6.3-2019	Floor and Trench Drains
A112.6.4-2003 (R2008)	Roof, Deck, and Balcony Drains
A112.6.7-2010 (R2019)	Sanitary Floor Sinks
A112.6.9-2005 (R2019)	Siphonic Roof Drains
A112.14.1-2003 (R2017)	Backwater Valves
A112.14.3-2018	Hydromechanical Grease Interceptors
A112.14.4-2001 (R2017)	Grease Removal Devices
A112.14.6-2010 (R2019)	FOG (Fats, Oils, and Greases) Disposal Systems
A112.18.1-2011/CSA B125.1-11 (R2017)	Plumbing Supply Fittings
A112.18.2-2015/CSA B125.2-15 (R2019)	Plumbing Waste Fittings
A112.18.3-2002 (R2017)	Performance Requirements for Backflow Protection Devices and Systems in Plumbing Fixture Fittings
A112.18.6-2009/CSA B125.6-09 (R2014)	Flexible Water Connectors
A112.18.8-2020	Sanitary Waste Valves for Plumbing Drainage Systems
A112.18.9-2011 (R2017)	Protectors/Insulators for Exposed Waste and Supplies on Accessible Fixtures
A112.19.1-2008/CSA B45.2-08	Enamelled Cast Iron and Enamelled Steel Plumbing Fixtures
A112.19.2-2008/CSA B45.1-08	Ceramic Plumbing Fixtures
A112.19.3-2008/CSA B45.4-08	Stainless Steel Plumbing Fixtures
A112.19.4M-1994 (R2004)	Porcelain Enameled Formed Steel Plumbing Fixtures
A112.19.5/CSA B45.15-2011 (R2016)	Flush Valves and Spuds for Water Closets, Urinals, and Tanks
A112.19.6-1995	Hydraulic Performance Requirements for Water Closets and Urinals
A112.19.7/CSA B45.10-2012 (R2017)	Hydromassage Bathtub Appliances
A112.19.9M-1991 (R2008)	Non-Vitreous Ceramic Plumbing Fixtures
A112.19.10-2017	Retrofit Dual Flush Devices for Water Closets
A112.19.12-2014 (R2019)	Wall Mounted, Pedestal Mounted, Adjustable, Elevating, Tilting, and Pivoting Lavatory, Sink, and Shampoo Bowl Carrier Systems and Drain Waste Systems
A112.19.13-2001 (R2007)	Electrohydraulic Water Closets
A112.19.14-2013 (R2018)	Six-Liter Water Closets Equipped With a Dual Flushing Device
A112.19.15-2012 (R2017)	Bathtubs/Whirlpool Bathtubs With Pressure Sealed Doors
A112.19.17-2010 (R2018)	Manufactured Safety Vacuum Release Systems (SVRS) for Residential and Commercial Swimming Pool, Spa, Hot Tub, and Wading Pool Suction Systems

A112.19.19-2006 (R2011)	Vitreous China Nonwater Urinals
A112.20.1-2004	Qualification of Installers of High Purity Piping Systems
A112.20.2-2004	Qualification of Installers of Firestop Systems and Devices for Piping Systems
A112.21.3M-1985 (R2017)	Hydrants for Utility and Maintenance Use
A112.36.2M-1991 (R2017)	Cleanouts

The ASME Publications Catalog shows a complete list of all the Standards published by the Society. For a complimentary catalog, or the latest information about our publications, call 1-800-THE-ASME (1-800-843-2763).

ASME Services

ASME is committed to developing and delivering technical information. At ASME's Customer Care, we make every effort to answer your questions and expedite your orders. Our representatives are ready to assist you in the following areas:

ASME Press	Member Services & Benefits	Public Information
<i>Codes & Standards</i>	Other ASME Programs	Self-Study Courses
Credit Card Orders	Payment Inquiries	Shipping Information
IMEchE Publications	Professional Development	Subscriptions/Journals/Magazines
Meetings & Conferences	Short Courses	Symposia Volumes
Member Dues Status	Publications	Technical Papers

How can you reach us? It's easier than ever!

There are four options for making inquiries* or placing orders. Simply mail, phone, fax, or E-mail us and a Customer Care representative will handle your request.

<i>Mail</i>	<i>Call Toll Free</i>	<i>Fax—24 hours</i>	<i>E-Mail—24 hours</i>
ASME	US & Canada: 800-THE-ASME	973-882-1717	customer-care@asme.org
150 Clove Road, 6th Floor	(800-843-2763)	973-882-5155	
Little Falls, New Jersey	Mexico: 95-800-THE-ASME		
07424-2139	(95-800-843-2763)		

*Customer Care staff are not permitted to answer inquiries about the technical content of this code or standard. Information as to whether or not technical inquiries are issued to this code or standard is shown on the copyright page. All technical inquiries must be submitted in writing to the staff secretary. Additional procedures for inquiries may be listed within.

ASME A112.18.8-2020

ISBN 978-0-7918-7358-8



9 780791 873588



J 1 8 0 2 Q