

ASME A112.19.10-2017

[Revision of ASME A112.19.10-2003 (R2008)]

Retrofit Dual Flush Devices for Water Closets

AN AMERICAN NATIONAL STANDARD



**The American Society of
Mechanical Engineers**

ASME A112.19.10-2017
[Revision of ASME A112.19.10-2003 (R2008)]

Retrofit Dual Flush Devices for Water Closets

AN AMERICAN NATIONAL STANDARD



**The American Society of
Mechanical Engineers**

Two Park Avenue • New York, NY • 10016 USA

Date of Issuance: February 21, 2018

This Standard will be revised when the Society approves the issuance of a new edition.

ASME issues written replies to inquiries concerning interpretations of technical aspects of this Standard. Interpretations are published on the Committee Web page and under <http://go.asme.org/InterpsDatabase>. Periodically certain actions of the ASME A112 Committee may be published as Cases. Cases are published on the ASME Web site under the A112 Committee Page at <http://go.asme.org/A112committee> as they are issued.

Errata to codes and standards may be posted on the ASME Web site under the Committee Pages to provide corrections to incorrectly published items, or to correct typographical or grammatical errors in codes and standards. Such errata shall be used on the date posted.

The A112 Committee Page can be found at <http://go.asme.org/A112committee>. There is an option available to automatically receive an e-mail notification when errata are posted to a particular code or standard. This option can be found on the appropriate Committee Page after selecting "Errata" in the "Publication Information" section.

ASME is the registered trademark of The American Society of Mechanical Engineers.

This code or standard was developed under procedures accredited as meeting the criteria for American National Standards. The Standards Committee that approved the code or standard was balanced to assure that individuals from competent and concerned interests have had an opportunity to participate. The proposed code or standard was made available for public review and comment that provides an opportunity for additional public input from industry, academia, regulatory agencies, and the public-at-large.

ASME does not "approve," "rate," or "endorse" any item, construction, proprietary device, or activity.

ASME does not take any position with respect to the validity of any patent rights asserted in connection with any items mentioned in this document, and does not undertake to insure anyone utilizing a standard against liability for infringement of any applicable letters patent, nor assume any such liability. Users of a code or standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, is entirely their own responsibility.

Participation by federal agency representative(s) or person(s) affiliated with industry is not to be interpreted as government or industry endorsement of this code or standard.

ASME accepts responsibility for only those interpretations of this document issued in accordance with the established ASME procedures and policies, which precludes the issuance of interpretations by individuals.

No part of this document may be reproduced in any form,
in an electronic retrieval system or otherwise,
without the prior written permission of the publisher.

The American Society of Mechanical Engineers
Two Park Avenue, New York, NY 10016-5990

Copyright © 2018 by
THE AMERICAN SOCIETY OF MECHANICAL ENGINEERS
All rights reserved
Printed in U.S.A.

CONTENTS

Foreword	iv
Committee Roster	v
Correspondence With the A112 Committee	vi
1 General	1
2 General Requirements	2
3 Testing	2
4 Markings and Installation Instructions	2

FOREWORD

The purpose of this Standard is to establish a nationally recognized standard for dual flush devices to achieve volumetric water saving performance for water closets. This Standard provides guidance to manufacturers, distributors, purchasers, and jurisdiction officials, specifiers, or water utility planners for water conservation, to promote better understanding between suppliers and users, and to furnish a basis for fair competition in furnishing such products to meet the principal demands of the trade.

This Standard includes a series of tests for retrofit dual flush devices for modification of the flush volume from installed water closets that use 1.28 gal per flush or a greater volume, to reduce water consumption, that may apply such control options to provide two distinctive modes of operation. The devices considered to be covered in this Standard are those required to provide at least a 30% reduction in water consumption in the reduced flush mode and still meet the required performance levels of the Standard.

The reduction in water closet flush volume discharges that may be made by a variety of techniques, other than one or another single motion selector actuation and leaving the unit, are not covered by this Standard. Other active or passive techniques, or methods not covered, include, but are not restricted to: installation of dams; displacement volume containers; cylindrical or other shaped water barrier containment elements; and hand-held observer, evaluator, and/or controls for termination of the flush. OEM devices are not covered by this Standard.

The tests specified in this Standard for the removal of liquid wastes and toilet tissues, or other comparable waste loads, are derived from industry experience, from field unit installations, independent laboratory evaluations by the methods included herein, and research studies. The endeavor accounts for service requirements that are necessary for the sanitary protection provided by water closets and water conservation achievable through the installation of these devices. The tests presented are from demonstrated applications by competent laboratory personnel and from other standards applications giving results of suitable reproducibility for the purposes intended.

ASME A112.19.10-1994 was the first edition of this Standard. The second edition, ASME A112.19.10-2003, changed the performance requirements to provide for an acceptable amount of leakage. In addition, soft metric conversion of the U.S. customary units were added and a number of minor editorial errors have been corrected.

This revision of the 2003 edition has changed the scope of this Standard to cover retrofit devices which are to be fitted into installed water closets that use 1.28 gal per flush or greater volume. This Standard was approved as an American National Standard on June 19, 2017.

ASME A112 COMMITTEE

Standardization of Plumbing Materials and Equipment

(The following is the roster of the Committee at the time of approval of this Standard.)

STANDARDS COMMITTEE OFFICERS

W. M. Smith, *Chair*
S. Rawalpindiwala, *Vice Chair*
A. L. Guzman Rodriguez, *Secretary*

STANDARDS COMMITTEE PERSONNEL

R. K. Adler , City of San Jose	L. A. Mercer , IAPMO
J. A. Ballanco , JB Engineering and Code Consulting	D. Orton , NSF International
J. E. Bertrand , Moen, Inc.	S. Rawalpindiwala , Kohler Co.
A. Bonlender , Bradley Corp.	S. A. Remedios , Remedios Consulting, LLC
R. Burnham , Zurn Industries, LLC	M. Sigler , Plumbing Manufacturers International
M. Campos , ICC Evaluation Service, LLC	G. L. Simmons , Charlotte Pipe & Foundry
W. E. Chapin , Professional Code Consulting, LLC	W. M. Smith , American Society of Plumbing Engineers
P. V. DeMarco , IAPMO	J. C. Watson , Elkay Manufacturing
N. E. Dickey , CSA Group	M. Weiss , Plumbing & Drainage Institute
G. S. Duren , Code Compliance, Inc.	W. C. Whitehead , Whitehead Consulting Services
R. Emmerson , Consultant	A. Ciechanowski , <i>Alternate</i> , NSF International
R. L. George , Plumb-Tech Design and Consulting Services, LLC	F. DiFolco , <i>Alternate</i> , CSA Group
A. L. Guzman Rodriguez , The American Society of Mechanical Engineers	D. Gleiberman , <i>Alternate</i> , Sloan Valve Co.
G. W. Harrison , Consultant	C. N. Gross , <i>Alternate</i> , IAPMO
L. Himmelblau , Chicago Faucet	D. Liang , <i>Alternate</i> , CSA Group
J. M. Koeller , Koeller and Co.	M. Malatesta , <i>Alternate</i> , American Standard
C. J. Lagan , American Standard	C. McLeod , <i>Alternate</i> , Kohler Co.
J. W. Lauer , Sloan Valve Co.	W. B. Morris , <i>Alternate</i> , Charlotte Pipe & Foundry
W. LeVan , Cast Iron Soil Pipe Institute	D. Viola , <i>Alternate</i> , IAPMO
D. Marbry , Fluidmaster, Inc.	S. L. Cavanaugh , <i>Contributing Member</i> , Cavanaugh Consulting
R. Mata , CSA Group	C. L. Jahrling , <i>Contributing Member</i> , ASSE International
	N. M. Kummerlen , <i>Contributing Member</i> , Consultant

A112.19.10 PROJECT TEAM — DUAL FLUSH DEVICES FOR WATER CLOSETS

M. Campos , <i>Chair</i> , ICC Evaluation Service, LLC	L. Himmelblau , Chicago Faucet
B. Antunez , BNC Crown of Creation	C. J. Lagan , American Standard
D. R. Berge , 5D Infusion Canada, Inc.	D. Marbry , Fluidmaster, Inc.
N. E. Dickey , CSA Group	S. Rawalpindiwala , Kohler Co.
D. Gleiberman , Sloan Valve Co.	R. L. Schnakenberg , Ariwesco, Inc.

CORRESPONDENCE WITH THE A112 COMMITTEE

General. ASME Standards are developed and maintained with the intent to represent the consensus of concerned interests. As such, users of this Standard may interact with the Committee by requesting interpretations, proposing revisions or a case, and attending Committee meetings. Correspondence should be addressed to:

Secretary, A112 Standards Committee
The American Society of Mechanical Engineers
Two Park Avenue
New York, NY 10016-5990
<http://go.asme.org/Inquiry>

Proposing Revisions. Revisions are made periodically to the Standard to incorporate changes that appear necessary or desirable, as demonstrated by the experience gained from the application of the Standard. Approved revisions will be published periodically.

The Committee welcomes proposals for revisions to this Standard. Such proposals should be as specific as possible, citing the paragraph number(s), the proposed wording, and a detailed description of the reasons for the proposal, including any pertinent documentation.

Proposing a Case. Cases may be issued to provide alternative rules when justified, to permit early implementation of an approved revision when the need is urgent, or to provide rules not covered by existing provisions. Cases are effective immediately upon ASME approval and shall be posted on the ASME Committee Web page.

Requests for Cases shall provide a Statement of Need and Background Information. The request should identify the Standard and the paragraph, figure, or table number(s), and be written as a Question and Reply in the same format as existing Cases. Requests for Cases should also indicate the applicable edition(s) of the Standard to which the proposed Case applies.

Interpretations. Upon request, the A112 Standards Committee will render an interpretation of any requirement of the Standard. Interpretations can only be rendered in response to a written request sent to the Secretary of the A112 Standards Committee.

Requests for interpretation should preferably be submitted through the online Interpretation Submittal Form. The form is accessible at <http://go.asme.org/InterpretationRequest>. Upon submittal of the form, the Inquirer will receive an automatic e-mail confirming receipt.

If the Inquirer is unable to use the online form, he/she may mail the request to the Secretary of the A112 Standards Committee at the above address. The request for an interpretation should be clear and unambiguous. It is further recommended that the Inquirer submit his/her request in the following format:

Subject:	Cite the applicable paragraph number(s) and the topic of the inquiry in one or two words.
Edition:	Cite the applicable edition of the Standard for which the interpretation is being requested.
Question:	Phrase the question as a request for an interpretation of a specific requirement suitable for general understanding and use, not as a request for an approval of a proprietary design or situation. Please provide a condensed and precise question, composed in such a way that a "yes" or "no" reply is acceptable.
Proposed Reply(ies):	Provide a proposed reply(ies) in the form of "Yes" or "No," with explanation as needed. If entering replies to more than one question, please number the questions and replies.
Background Information:	Provide the Committee with any background information that will assist the Committee in understanding the inquiry. The Inquirer may also include any plans or drawings that are necessary to explain the question; however, they should not contain proprietary names or information.

Requests that are not in the format described above may be rewritten in the appropriate format by the Committee prior to being answered, which may inadvertently change the intent of the original request.

Moreover, ASME does not act as a consultant for specific engineering problems or for the general application or understanding of the Standard requirements. If, based on the inquiry information submitted, it is the opinion of the Committee that the inquirer should seek assistance, the inquiry will be returned with the recommendation that such assistance be obtained.

ASME procedures provide for reconsideration of any interpretation when or if additional information that might affect an interpretation is available. Further, persons aggrieved by an interpretation may appeal to the cognizant ASME Committee or Subcommittee. ASME does not “approve,” “certify,” “rate,” or “endorse” any item, construction, proprietary device, or activity.

Attending Committee Meetings. The A112 Standards Committee regularly holds meetings and/or telephone conferences that are open to the public. Persons wishing to attend any meeting and/or telephone conference should contact the Secretary of the A112 Standards Committee. Future Committee meeting dates and locations can be found on the Committee Page at <http://go.asme.org/A112committee>.

INTENTIONALLY LEFT BLANK

RETROFIT DUAL FLUSH DEVICES FOR WATER CLOSETS

1 GENERAL

1.1 Scope

This Standard establishes physical, material, testing, and marking requirements for retrofit dual flush devices that are installed within gravity-type water closet tanks and have a full flush volume of 4.8 Lpf (1.28 gpf) or greater volume.

1.2 Units of Measurement

The values stated in either SI (metric) or U.S. Customary (inch/pound) units of measure are to be regarded as the standard. In this Standard, the inch/pound units are shown in parentheses. The values stated in each measurement system are equivalent in application; however, each system is to be used independently. Combining values from the two measurement systems can result in nonconformance with this Standard. All references to gallons are to U.S. gallons.

1.3 References

The following document forms a part of this Standard to the extent specified herein. Unless otherwise specified, the latest edition shall apply.

ASME A112.19.5/CSA B45.15, Flush Valves and Spuds for Water Closets, Urinals, and Tanks

Publisher: The American Society of Mechanical Engineers (ASME), Two Park Avenue, New York, NY 10016-5990
(www.asme.org)

1.4 Definitions

cycle time: the time beginning at the instant the flush release device is operated, and ending at the instant the water supply valve is completely shut off and the water stops flowing.

dual flush device: a mechanism for control of water closet discharge that provides the user with two options for selective operation with either a normal fill volume or a reduced volume of water from the tank.

flapper valve: see *flush valve*.

flowing pressure: the pressure in a water supply pipe at the inlet to an open valve.

flush tank (gravity type): a vessel that stores a predetermined quantity of water and includes a flushing device to discharge water (plus some through-flow from the water supply line) into a water closet bowl or urinal.

NOTE: A common type of flush tank is a wall-hung vessel or a vessel close-coupled with the water closet bowl that is fitted with a fill valve and flush valve.

flush valve: a valve located in a flush tank and used to flush a fixture by discharging water into the fixture.

sanitary: reasonably acceptable appearance and not necessarily microbiologically clean.

water closet: a plumbing fixture having a water-containing receptor that receives liquid and solid body waste and, upon actuation, conveys the waste through an exposed integral trap seal into a gravity drainage system.

water savings: the amount of flush volume water reduction in gallons or percentage when comparing consumption with and without a dual flush device for a water closet.

water surface: the surface of the still water in the water closet bowl when filled to the trap weir.

2 GENERAL REQUIREMENTS

2.1 Functional Operation

The flush valve with dual flush feature shall be designed for retrofit use in water closets and shall fit within the tank punching without interference with other operating parts. The user shall be required to activate a full or reduced flush by actuation of the selector control. After release, the selected flush mode shall be completed without requiring further action or holding by the user.

2.2 Flush Valve

The flush valve shall meet the following requirements of ASME A112.19.5/CSA B45.15:

- (a) rated temperature
- (b) threads
- (c) overflow tube
- (d) thread torque test
- (e) fixture and flush valve leak test
- (f) leak rate and chemical resistance test

3 TESTING

3.1 Life Cycle Testing

The flush valve with dual flush device shall be evaluated for durability. The life cycle test shall be conducted as follows:

- (a) Install the specimen with a minimum sustained water head of 150 mm (6.0 in.) at $21^{\circ}\text{C} \pm 5^{\circ}\text{C}$ ($70^{\circ}\text{F} \pm 10^{\circ}\text{F}$).
- (b) Operate the specimen and allow it to return to its closed position for 30,000 cycles using a sequence of reduced to full flushes in a ratio of 1:4. After completing 30,000 cycles at a ratio of 1:4, immediately begin 120,000 cycles in the reduced flush volume mode.

3.2 Performance Requirements

During and after the test, dual flush devices shall

- (a) continue to function as they did at the beginning of the test
- (b) show no signs of leakage
- (c) not develop any defects that might adversely affect their functionality or serviceability

4 MARKINGS AND INSTALLATION INSTRUCTIONS

4.1 Markings

Retrofit dual flush devices shall be marked with the manufacturer's name and/or registered trademark or, in case of private labeling, the name for whom the device was manufactured.

Markings shall be permanent, legible, and visible after installation.

4.1.1 Repair Parts. Devices shall have a label indicating at least the following:

- (a) the telephone number of a service department from which end-users can obtain replacement parts
- (b) the serial or part number
- (c) information on procuring replacement parts for maintaining the flush volume

4.2 Installation

Installation instructions shall include the following provisions:

- (a) the procedures necessary to provide a full volume flush and procedures to establish a partial volume flush consistent with the requirements in [para. 2.1](#)
- (b) the steps necessary to ensure that the dual flush actuation selector and all parts move freely when the tank is empty and normally filled

4.3 Product Limitations to Specific Water Closets

Restrictions or limitations on the installation of the device(s) to any single or group of manufacturers' water closets shall be specified on a label on the package or instructions by the manufacturer, producer, or provider of the device(s).

A112 ASME STANDARDS RELATED TO PLUMBING

A112.1.2-2012 (R2017)	Air Gaps in Plumbing Systems (For Plumbing Fixtures and Water-Connected Receptors)
A112.1.3-2000 (R2015)	Air Gap Fittings for Use With Plumbing Fixtures, Appliances, and Appurtenances
A112.3.1-2007 (R2017)	Stainless Steel Drainage Systems for Sanitary, DWV, Storm, and Vacuum Applications, Above- and Below-Ground
A112.3.4-2000 (R2004)	Macerating Toilet Systems and Related Components
A112.4.1-2009 (R2014)	Water Heater Relief Valve Drain Tubes
A112.4.2-2009 (R2014)	Water Closet Personal Hygiene Devices
A112.4.3-1999 (R2015)	Plastic Fittings for Connecting Water Closets to the Sanitary Drainage System
A112.4.4-2017	Plastic Push-Fit Drain, Waste, and Vent (DWV) Fittings
A112.4.7-2002 (R2008)	Point of Use and Branch Water Submetering Systems
A112.4.14-2004 (R2010)	Manually Operated, Quarter-Turn Shutoff Valves for Use in Plumbing Systems
A112.6.1M-1997 (R2017)	Floor-Affixed Supports for Off-the-Floor Plumbing Fixtures for Public Use
A112.6.2-2017	Framing-Affixed Supports (Carriers) for Off-the-Floor Plumbing Fixtures
A112.6.3-2016	Floor and Trench Drains
A112.6.4-2003 (R2008)	Roof, Deck, and Balcony Drains
A112.6.7-2011 (R2015)	Sanitary Floor Sinks
A112.6.9-2010 (R2015)	Siphonic Roof Drains
A112.14.1-2003 (R2017)	Backwater Valves
A112.14.3-2000 (R2004)	Grease Interceptors
A112.14.4-2001 (R2017)	Grease Removal Devices
A112.14.6-2010 (R2015)	FOG (Fats, Oils, and Greases) Disposal Systems
A112.18.1-2011/CSA B125.1-11 (R2017)	Plumbing Supply Fittings
A112.18.2-2011/CSA B125.2-11	Plumbing Waste Fittings
A112.18.3-2002 (R2017)	Performance Requirements for Backflow Protection Devices and Systems in Plumbing Fixture Fittings
A112.18.6-2009/CSA B125.6-09 (R2014)	Flexible Water Connectors
A112.18.8-2009 (R2014)	In-Line Sanitary Waste Valves for Plumbing Drainage Systems
A112.18.9-2011 (R2017)	Protectors/Insulators for Exposed Waste and Supplies on Accessible Fixtures
A112.19.1-2008/CSA B45.2-08	Enamelled Cast Iron and Enamelled Steel Plumbing Fixtures
A112.19.2-2008/CSA B45.1-08	Ceramic Plumbing Fixtures
A112.19.3-2008/CSA B45.4-08	Stainless Steel Plumbing Fixtures
A112.19.4M-1994 (R2004)	Porcelain Enameled Formed Steel Plumbing Fixtures
A112.19.5/CSA B45.15-2011 (R2016)	Flush Valves and Spuds for Water Closets, Urinals, and Tanks
A112.19.6-1995	Hydraulic Performance Requirements for Water Closets and Urinals
A112.19.7/CSA B45.10-2012 (R2017)	Hydromassage Bathtub Appliances
A112.19.9M-1991 (R2008)	Non-Vitreous Ceramic Plumbing Fixtures
A112.19.10-2017	Retrofit Dual Flush Devices for Water Closets
A112.19.12-2014	Wall Mounted, Pedestal Mounted, Adjustable, Elevating, Tilting, and Pivoting Lavatory, Sink, and Shampoo Bowl Carrier Systems and Drain Waste Systems
A112.19.13-2001 (R2007)	Electrohydraulic Water Closets
A112.19.14-2013	Six-Liter Water Closets Equipped With a Dual Flushing Device
A112.19.15-2012 (R2017)	Bathtubs/Whirlpool Bathtubs With Pressure Sealed Doors
A112.19.17-2010	Manufactured Safety Vacuum Release Systems (SVRS) for Residential and Commercial Swimming Pool, Spa, Hot Tub, and Wading Pool Suction Systems
A112.19.19-2006 (R2011)	Vitreous China Nonwater Urinals
A112.20.1-2004	Qualification of Installers of High Purity Piping Systems
A112.20.2-2004	Qualification of Installers of Firestop Systems and Devices for Piping Systems

A112.21.3M-1985 (R2017)	Hydrants for Utility and Maintenance Use
A112.36.2M-1991 (R2017)	Cleanouts

The ASME Publications Catalog shows a complete list of all the Standards published by the Society. For a complimentary catalog, or the latest information about our publications, call 1-800-THE-ASME (1-800-843-2763).

ASME A112.19.10-2017

ISBN 978-0-7918-7162-1



9 780791 871621



J 1381 T